Package 'mlr3viz'

September 23, 2026

Title Visualizations for 'mlr3'

Version 0.11.2

Description Visualization package of the 'mlr3' ecosystem. It features plots for mlr3 objects such as tasks, learners, predictions, benchmark results, tuning instances and filters via the 'autoplot()' generic of 'ggplot2'. The package draws plots with the 'viridis' color palette and applies the minimal theme. Visualizations include barplots, boxplots, histograms, ROC curves, and Precision-Recall curves.

License LGPL-3

URL https://mlr3viz.mlr-org.com, https://github.com/mlr-org/mlr3viz

BugReports https://github.com/mlr-org/mlr3viz/issues

Depends R (>= 3.3.0), mlr3 (>= 1.3.0)

Imports checkmate, data.table, ggplot2 (>= 3.3.0), mlr3misc (>= 0.7.0), scales, stats, utils, viridis

Suggests bbotk (>= 1.0.0), clue, cluster, GGally, ggdendro, ggfortify (>= 0.4.11), ggparty, glmnet, knitr, lgr, mlr3cluster, mlr3filters, mlr3fselect (>= 1.7.0), mlr3inferr, mlr3learners, mlr3tuning (>= 1.0.0), paradox, partykit, patchwork (>= 1.1.1), precrec (>= 0.24.0), ranger, rpart, testthat (>= 3.0.0), vdiffr (>= 1.0.2), xgboost

Config/testthat/edition 3

Config/testthat/parallel true

Encoding UTF-8

NeedsCompilation no

Collate 'BenchmarkResult.R' 'Filter.R' 'LearnerClassif.R' 'LearnerClassifCVGlmnet.R' 'LearnerClassifGlmnet.R' 'LearnerClassifRpart.R' 'LearnerClustHierarchical.R' 'LearnerRegr.R' 'LearnerRegrCVGlmnet.R' 'LearnerRegrGlmnet.R' 'LearnerRegrRpart.R' 'OptimInstanceBatchSingleCrit.R' 'Prediction.R' 'PredictionClassif.R' 'PredictionClust.R' 'PredictionRegr.R' 'ResampleResult.R' 'Task.R' 'TaskClassif.R'

'TaskClust.R' 'TaskRegr.R' 'TuningInstanceBatchSingleCrit.R'
'EnsembleFSResult.R' 'as_precrec.R' 'bibentries.R' 'helper.R'
'plot_learner_prediction.R' 'reexports.R' 'zzz.R'

Config/roxygen2/version 8.1.0

Author Michel Lang [aut] (ORCID: <https://orcid.org/0000-0001-9754-0393>),
Patrick Schratz [aut] (ORCID: <https://orcid.org/0000-0003-0748-6624>),
Raphael Sonabend [aut] (ORCID: <https://orcid.org/0000-0001-9225-4654>),
Marc Becker [cre, aut] (ORCID: <https://orcid.org/0000-0002-8115-0400>),
Jakob Richter [aut] (ORCID: <https://orcid.org/0000-0003-4481-5554>),
Damir Pulatov [ctb],
John Zobolas [aut] (ORCID: <https://orcid.org/0000-0002-3609-8674>)

Maintainer Marc Becker <marcbecker@posteo.de>

Repository CRAN

Date/Publication 2026-09-23 15:10:09 UTC

Contents

mlr3viz-package . . . 3
as_precrec . . . 4
autoplot.BenchmarkResult . . . 4
autoplot.EnsembleFSResult . . . 6
autoplot.Filter . . . 8
autoplot.LearnerClassif . . . 9
autoplot.LearnerClassifCVGlmnet . . . 10
autoplot.LearnerClassifRpart . . . 12
autoplot.LearnerClustHierarchical . . . 13
autoplot.LearnerRegr . . . 15
autoplot.OptimInstanceBatchSingleCrit . . . 16
autoplot.PredictionClassif . . . 18
autoplot.PredictionClust . . . 20
autoplot.PredictionRegr . . . 21
autoplot.ResampleResult . . . 22
autoplot.TaskClassif . . . 24
autoplot.TaskClust . . . 25
autoplot.TaskRegr . . . 26
autoplot.TuningInstanceBatchSingleCrit . . . 27
plot_learner_prediction . . . 29
predict_grid . . . 30

Index **31**

mlr3viz-package *mlr3viz: Visualizations for 'mlr3'*

Description

Visualization package of the 'mlr3' ecosystem. It features plots for mlr3 objects such as tasks, learners, predictions, benchmark results, tuning instances and filters via the 'autoplot()' generic of 'ggplot2'. The package draws plots with the 'viridis' color palette and applies the minimal theme. Visualizations include barplots, boxplots, histograms, ROC curves, and Precision-Recall curves.

Author(s)

Maintainer: Marc Becker <marcbecker@posteo.de> (ORCID)

Authors:

- Marc Becker <marcbecker@posteo.de> (ORCID)
- Michel Lang <michellang@gmail.com> (ORCID)
- Patrick Schratz <patrick.schratz@gmail.com> (ORCID)
- Raphael Sonabend <raphael.sonabend.15@ucl.ac.uk> (ORCID)
- Jakob Richter <jakob1richter@gmail.com> (ORCID)
- John Zobolas <bblodfon@gmail.com> (ORCID)

Other contributors:

- Damir Pulatov <dpulatov@uwyo.edu> [contributor]

See Also

Useful links:

- https://mlr3viz.mlr-org.com
- https://github.com/mlr-org/mlr3viz
- Report bugs at https://github.com/mlr-org/mlr3viz/issues

as_precrec *Convert to 'precrec' Format*

Description

Converts to a format which is understood by `precrec::evalmod()` of package **precrec**.

Usage

```
as_precrec(object)

## S3 method for class 'PredictionClassif'
as_precrec(object)

## S3 method for class 'ResampleResult'
as_precrec(object)

## S3 method for class 'BenchmarkResult'
as_precrec(object)
```

Arguments

`object`	(any) Object to convert.

Value

Object as created by `precrec::mmdata()`.

References

Saito T, Rehmsmeier M (2017). "Precrec: fast and accurate precision-recall and ROC curve calculations in R." *Bioinformatics*, **33**(1), 145-147. doi:10.1093/bioinformatics/btw570.

autoplot.BenchmarkResult *Plots for Benchmark Results*

Description

Visualizations for mlr3::BenchmarkResult. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"boxplot"` (default): Boxplots of performance measures, one box per mlr3::Learner and one facet per mlr3::Task.

- "roc": ROC curve (1 - specificity on x, sensitivity on y). The mlr3::BenchmarkResult may only have a single mlr3::Task and a single mlr3::Resampling. Note that you can subset any mlr3::BenchmarkResult with its $filter() method (see examples). Requires package **precrec**.
- "prc": Precision recall curve. See "roc".
- "ci": Plot confidence intervals. Pass a msr("ci", ...) from the mlr3inferr package as argument measure.

Usage

```
## S3 method for class 'BenchmarkResult'
autoplot(
  object,
  type = "boxplot",
  measure = NULL,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(mlr3::BenchmarkResult).
type	(character(1)): Type of the plot. See description.
measure	(mlr3::Measure) Performance measure to use.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	arguments passed on to precrec::autoplot() for type = "roc" or "prc". Useful to e.g. remove confidence bands with show_cb = FALSE.

Value

ggplot2::ggplot().

References

Saito T, Rehmsmeier M (2017). "Precrec: fast and accurate precision-recall and ROC curve calculations in R." *Bioinformatics*, **33**(1), 145-147. doi:10.1093/bioinformatics/btw570.

Examples

```
if (mlr3misc::require_namespaces("precrec", quietly = TRUE)) {
tasks = tsks(c("breast_cancer", "sonar"))
learner = lrns(c("classif.featureless", "classif.rpart"), predict_type = "prob")
resampling = rsmps("cv")
object = benchmark(benchmark_grid(tasks, learner, resampling))
```

```
head(fortify(object))
autoplot(object)
autoplot(object$clone(deep = TRUE)$filter(task_ids = "sonar"), type = "roc")
}
```

`autoplot.EnsembleFSResult`

Plots for Ensemble Feature Selection Results

Description

Visualizations for EnsembleFSResult. The argument `type` determines the type of plot generated. The available options are:

- `"pareto"` (default): Scatterplot of performance versus the number of features, possibly including the **Pareto front**, which allows users to decide how much performance they are willing to trade off for a more sparse model.
- `"performance"`: Boxplot of performance across the different learners used in the ensemble feature selection process. Each box represents the distribution of scores across different resampling iterations for a particular learner.
- `"n_features"`: Boxplot of the number of features selected by each learner in the different resampling iterations.
- `"stability"`: Barplot of stability score for each learner used in the ensemble feature selection. This plot shows how similar are the output feature sets from each learner across the different resamplings.

Usage

```
## S3 method for class 'EnsembleFSResult'
autoplot(
  object,
  type = "pareto",
  pareto_front = "stepwise",
  stability_measure = "jaccard",
  stability_args = NULL,
  theme = theme_minimal(),
  ...
)
```

Arguments

`object`	(mlr3fselect::EnsembleFSResult).
`type`	(character(1)): Type of the plot. See description.

`pareto_front` (`character(1)`)
Type of pareto front to plot. Can be `"stepwise"` (default), `"estimated"` or `"none"`.

`stability_measure`
(`character(1)`)
The stability measure to be used in case `type = "stability"`. One of the measures returned by `stabm::listStabilityMeasures()` in lower case. Default is `"jaccard"`.

`stability_args` (`list`)
Additional arguments passed to the stability measure function.

`theme` (`ggplot2::theme()`)
The `ggplot2::theme_minimal()` is applied by default to all plots.

`...` (ignored).

Value

`ggplot2::ggplot()`.

Examples

```
if (mlr3misc::require_namespaces("mlr3fselect", quietly = TRUE)) {

  set.seed (42)
  library(mlr3fselect)

  efsr = ensemble_fselect(
    fselector = fs("random_search"),
    task = tsk("sonar"),
    learners = lrns(c("classif.rpart", "classif.featureless")),
    init_resampling = rsmp("subsampling", repeats = 5),
    inner_resampling = rsmp("cv", folds = 3),
    inner_measure = msr("classif.ce"),
    measure = msr("classif.acc"),
    terminator = trm("evals", n_evals = 5)
  )

  # Pareto front (default, stepwise)
  autoplot(efsr)

  # Pareto front (estimated)
  autoplot(efsr, pareto_front = "estimated")

  # Performance
  autoplot(efsr, type = "performance")

  # Number of features
  autoplot(efsr, type = "n_features")

  # stability
  autoplot(efsr, type = "stability")
```

```
  # use inner measure
  efsr$set_active_measure("inner")

  # Pareto front uses now the classification error
  autoplot(efsr)

}
```

`autoplot.Filter` *Plots for Filter Scores*

Description

Visualizations for mlr3filters::Filter. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"barplot"` (default): Bar plot of filter scores.

Usage

```
## S3 method for class 'Filter'
autoplot(object, type = "boxplot", n = Inf, theme = theme_minimal(), ...)
```

Arguments

`object`	(mlr3filters::Filter).
`type`	(character(1)): Type of the plot. See description.
`n`	(`integer(1)`) Only include the first `n` features with the highest importance. Defaults to all features.
`theme`	(`ggplot2::theme()`) The `ggplot2::theme_minimal()` is applied by default to all plots.
`...`	(ignored).

Value

`ggplot2::ggplot()`.

Examples

```
if (mlr3misc::require_namespaces("mlr3filters", quietly = TRUE)) {
library(mlr3filters)

task = tsk("mtcars")
f = flt("correlation")
f$calculate(task)
```

```
head(fortify(f))
autoplot(f, n = 5)
}
```

`autoplot.LearnerClassif` *Plot for Classification Learners*

Description

Visualizations for mlr3::LearnerClassif. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"prediction"` (default): Decision boundary of the learner and the true class labels.

Usage

```
## S3 method for class 'LearnerClassif'
autoplot(
  object,
  type = "prediction",
  task,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)
```

Arguments

`object`	(mlr3::LearnerClassif).
`type`	(character(1)): Type of the plot. See description.
`task`	(mlr3::Task) Train task.
`grid_points`	(integer(1)) Number of grid points per feature dimension.
`expand_range`	(numeric(1)) Expand the range of the grid.
`theme`	(`ggplot2::theme()`) The `ggplot2::theme_minimal()` is applied by default to all plots.
`...`	(ignored).

Value

`ggplot2::ggplot()`.

Examples

```
task = tsk("sonar")$select(c("V1", "V11"))
learner = lrn("classif.rpart", predict_type = "prob")
learner$train(task)

autoplot(learner, type = "prediction", task)
```

`autoplot.LearnerClassifCVGlmnet`
Plots for GLMNet Learners

Description

Visualizations for mlr3learners::LearnerClassifGlmnet. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"prediction"` (default): Decision boundary of the learner and the true class labels.
- `"ggfortify"`: Visualizes the model using the package **ggfortify**.

Usage

```
## S3 method for class 'LearnerClassifCVGlmnet'
autoplot(
  object,
  type = "prediction",
  task = NULL,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)

## S3 method for class 'LearnerClassifGlmnet'
autoplot(
  object,
  type = "prediction",
  task = NULL,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)

## S3 method for class 'LearnerRegrCVGlmnet'
autoplot(
  object,
```

```
  type = "prediction",
  task = NULL,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)

## S3 method for class 'LearnerRegrGlmnet'
autoplot(
  object,
  type = "prediction",
  task = NULL,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(mlr3learners::LearnerClassifGlmnet | mlr3learners::LearnerRegrGlmnet | mlr3learners::LearnerClassifC | mlr3learners::LearnerRegrCVGlmnet).
type	(character(1)): Type of the plot. See description.
task	(mlr3::Task) Train task.
grid_points	(integer(1)) Number of grid points per feature dimension.
expand_range	(numeric(1)) Expand the range of the grid.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

References

Tang Y, Horikoshi M, Li W (2016). "ggfortify: Unified Interface to Visualize Statistical Result of Popular R Packages." *The R Journal*, **8**(2), 474–485. doi:10.32614/RJ2016060.

Examples

```
if (mlr3misc::require_namespaces("mlr3learners", quietly = TRUE)) {
## Not run:
```

```
library(mlr3learners)

# classification
task = tsk("sonar")
learner = lrn("classif.glmnet")
learner$train(task)
autoplot(learner, type = "ggfortify")

# regression
task = tsk("mtcars")
learner = lrn("regr.glmnet")
learner$train(task)
autoplot(learner, type = "ggfortify")

## End(Not run)
}
```

`autoplot.LearnerClassifRpart` *Plots for Rpart Learners*

Description

Visualizations for mlr3::LearnerClassifRpart. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"prediction"` (default): Decision boundary of the learner and the true class labels.
- `"ggparty"`: Visualizes the tree using the package **ggparty**.

Usage

```
## S3 method for class 'LearnerClassifRpart'
autoplot(
  object,
  type = "prediction",
  task = NULL,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)

## S3 method for class 'LearnerRegrRpart'
autoplot(
  object,
  type = "prediction",
  task = NULL,
  grid_points = 100L,
```

```
  expand_range = 0,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(mlr3::LearnerClassifRpart | mlr3::LearnerRegrRpart).
type	(character(1)): Type of the plot. See description.
task	(mlr3::Task) Train task.
grid_points	(integer(1)) Number of grid points per feature dimension.
expand_range	(numeric(1)) Expand the range of the grid.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces(c("partykit", "ggparty"), quietly = TRUE)) {
# classification
task = tsk("iris")
learner = lrn("classif.rpart", keep_model = TRUE)
learner$train(task)
autoplot(learner, type = "ggparty")

# regression
task = tsk("mtcars")
learner = lrn("regr.rpart", keep_model = TRUE)
learner$train(task)
autoplot(learner, type = "ggparty")
}
```

---

autoplot.LearnerClustHierarchical

Plots for Hierarchical Clustering Learners

Description

Visualizations for hierarchical clusters. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"dend"` (default): Dendrograms using **ggdendro** package.
- `"scree"`: Scree plot that shows the number of possible clusters on the x-axis and the height on the y-axis.

Usage

```
## S3 method for class 'LearnerClustHierarchical'
autoplot(
  object,
  type = "dend",
  task = NULL,
  theme = theme_minimal(),
  theme_dendro = TRUE,
  ...
)
```

Arguments

`object`	(mlr3cluster::LearnerClustAgnes | mlr3cluster::LearnerClustDiana | mlr3cluster::LearnerClustHclust).
`type`	(character(1)): Type of the plot. See description.
`task`	(mlr3::Task) Optionally, pass the task to add labels of observations to a `hclust` dendrogram. Labels are set via the row names of the task.
`theme`	(`ggplot2::theme()`) The `ggplot2::theme_minimal()` is applied by default to all plots.
`theme_dendro`	(`logical(1)`) If `TRUE` (default), the special dendrogram theme from **ggdendro** package is used in plot `"dend"`. Set to `FALSE` to use the theme passed in `theme`.
`...`	(ignored).

Value

`ggplot2::ggplot()`.

Examples

```
if (mlr3misc::require_namespaces("mlr3cluster", quietly = TRUE)) {
library(mlr3cluster)

task = tsk("usarrests")

# agnes clustering
learner = lrn("clust.agnes")
```

```
learner$train(task)
autoplot(learner)

# diana clustering
learner = lrn("clust.diana")
learner$train(task)
autoplot(learner)

# hclust clustering
learner = lrn("clust.hclust")
learner$train(task)
autoplot(learner, type = "scree")
}
```

`autoplot.LearnerRegr` *Plot for Regression Learners*

Description

Visualizations for mlr3::LearnerRegr. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"prediction"` (default): Decision boundary of the learner and the true class labels.

Usage

```
## S3 method for class 'LearnerRegr'
autoplot(
  object,
  type = "prediction",
  task,
  grid_points = 100L,
  expand_range = 0,
  theme = theme_minimal(),
  ...
)
```

Arguments

`object`	(mlr3::LearnerRegr).
`type`	(character(1)): Type of the plot. See description.
`task`	(mlr3::Task) Train task.
`grid_points`	(integer(1)) Number of grid points per feature dimension.
`expand_range`	(numeric(1)) Expand the range of the grid.

theme (ggplot2::theme())
The ggplot2::theme_minimal() is applied by default to all plots.

... (ignored).

Value

ggplot2::ggplot().

Examples

```
task = tsk("mtcars")$select(c("am", "carb"))
learner = lrn("regr.rpart")
learner$train(task)

autoplot(learner, type = "prediction", task)
```

---

autoplot.OptimInstanceBatchSingleCrit

Plots for Optimization Instances

Description

Visualizations for bbotk::OptimInstanceBatchSingleCrit. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"marginal"` (default): Scatter plots of x versus y. The color of the points shows the batch number.
- `"performance"`: Scatter plots of batch number versus y
- `"parameter"`: Scatter plots of batch number versus input. The color of the points shows the y values.
- `"parallel"`: Parallel coordinates plot. x values are rescaled by `(x - mean(x)) / sd(x)`.
- `"points"`: Scatter plot of two x dimensions versus y values. The color of the points shows the y values.
- `"surface"`: Surface plot of two x dimensions versus y values. The y values are interpolated with the supplied mlr3::Learner.
- `"pairs"`: Plots all x and y values against each other.
- `"incumbent"`: Plots the incumbent versus the number of configurations.

Usage

```
## S3 method for class 'OptimInstanceBatchSingleCrit'
autoplot(
  object,
  type = "marginal",
  cols_x = NULL,
  trafo = FALSE,
  learner = mlr3::lrn("regr.ranger"),
  grid_resolution = 100,
  batch = NULL,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(bbotk::OptimInstanceBatchSingleCrit).
type	(character(1)): Type of the plot. See description.
cols_x	(character()) Column names of x values. By default, all untransformed x values from the search space are plotted. Transformed hyperparameters are prefixed with x_domain_.
trafo	(logical(1)) If FALSE (default), the untransformed x values are plotted. If TRUE, the transformed x values are plotted.
learner	(mlr3::Learner) Regression learner used to interpolate the data of the surface plot.
grid_resolution	(numeric()) Resolution of the surface plot.
batch	(integer()) The batch number(s) to limit the plot to. The default is all batches.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces(c("paradox", "bbotk", "patchwork"), quietly = TRUE)) {
library(bbotk)

fun = function(xs) {
  c(y = -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + 10)
```

```
}
domain = ps(
  x1 = p_dbl(-10, 10),
  x2 = p_dbl(-5, 5)
)
codomain = ps(
  y = p_dbl(tags = "maximize")
)
obfun = ObjectiveRFun$new(
  fun = fun,
  domain = domain,
  codomain = codomain
)

instance = oi(objective = obfun, terminator = trm("evals", n_evals = 20))

optimizer = opt("random_search", batch_size = 2)
optimizer$optimize(instance)

# plot y versus batch number
print(autoplot(instance, type = "performance"))

# plot x1 values versus performance
print(autoplot(instance, type = "marginal", cols_x = "x1"))

# plot parallel coordinates plot
print(autoplot(instance, type = "parallel"))

# plot pairs
print(autoplot(instance, type = "pairs"))

# plot incumbent
print(autoplot(instance, type = "incumbent"))
}
```

`autoplot.PredictionClassif`

Plots for Classification Predictions

Description

Visualizations for mlr3::PredictionClassif. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"stacked"` (default): Stacked barplot of true and estimated class labels.
- `"roc"`: ROC curve (1 - specificity on x, sensitivity on y). Requires package **precrec**.
- `"prc"`: Precision recall curve. Requires package **precrec**.
- `"threshold"`: Systematically varies the threshold of the mlr3::PredictionClassif object and plots the resulting performance as returned by `measure`.

Usage

```
## S3 method for class 'PredictionClassif'
autoplot(
  object,
  type = "stacked",
  measure = NULL,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(mlr3::PredictionClassif).
type	(character(1)): Type of the plot. See description.
measure	(mlr3::Measure) Performance measure to use.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

References

Saito T, Rehmsmeier M (2017). "Precrec: fast and accurate precision-recall and ROC curve calculations in R." *Bioinformatics*, **33**(1), 145-147. doi:10.1093/bioinformatics/btw570.

Examples

```
if (mlr3misc::require_namespaces("precrec", quietly = TRUE)) {
task = tsk("spam")
learner = lrn("classif.rpart", predict_type = "prob")
object = learner$train(task)$predict(task)

head(fortify(object))
autoplot(object)
autoplot(object, type = "roc")
autoplot(object, type = "prc")
}
```

`autoplot.PredictionClust` *Plots for Cluster Predictions*

Description

Visualizations for mlr3cluster::PredictionClust. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"scatter"` (default): scatterplot with correlation values and colored cluster assignments.
- `"sil"`: Silhouette plot with mean silhouette value as the reference line. Requires package **ggfortify**.
- `"pca"`: Perform PCA on data and color code cluster assignments. Inspired by and uses ggfortify::autoplot.kmeans.

Usage

```
## S3 method for class 'PredictionClust'
autoplot(
  object,
  task,
  row_ids = NULL,
  type = "scatter",
  theme = theme_minimal(),
  ...
)
```

Arguments

`object`	(mlr3cluster::PredictionClust).
`task`	(mlr3cluster::TaskClust).
`row_ids`	(`integer()`) Row ids to subset task data to ensure that only the data used to make predictions are shown in plots.
`type`	(character(1)): Type of the plot. See description.
`theme`	(`ggplot2::theme()`) The `ggplot2::theme_minimal()` is applied by default to all plots.
`...`	(ignored).

Value

`ggplot2::ggplot()`.

References

Tang Y, Horikoshi M, Li W (2016). "ggfortify: Unified Interface to Visualize Statistical Result of Popular R Packages." *The R Journal*, **8**(2), 474–485. doi:10.32614/RJ2016060.

Examples

```
if (mlr3misc::require_namespaces(c("clue", "mlr3cluster"), quietly = TRUE)) {
library(mlr3cluster)

task = tsk("usarrests")
learner = lrn("clust.kmeans", centers = 3)
object = learner$train(task)$predict(task)

head(fortify(object))
autoplot(object, task)
}
```

`autoplot.PredictionRegr`

Plots for Regression Predictions

Description

Visualizations for mlr3::PredictionRegr. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"xy"` (default): Scatterplot of "true" response vs. "predicted" response. By default a linear model is fitted via `geom_smooth(method = "lm")` to visualize the trend between x and y (by default colored blue). In addition `geom_abline()` with `slope = 1` is added to the plot. Note that `geom_smooth()` and `geom_abline()` may overlap, depending on the given data.
- `"histogram"`: Histogram of residuals: $r = y - \hat{y}$.
- `"residual"`: Plot of the residuals, with the response $\hat{y}$ on the "x" and the residuals on the "y" axis. By default a linear model is fitted via `geom_smooth(method = "lm")` to visualize the trend between x and y (by default colored blue).
- `"confidence"`: Scatterplot of "true" response vs. "predicted" response with confidence intervals. Error bars calculated as object$response +- quantile * object$se and so only possible with `predict_type = "se"`. `geom_abline()` with `slope = 1` is added to the plot.

Usage

```
## S3 method for class 'PredictionRegr'
autoplot(
  object,
  type = "xy",
  binwidth = NULL,
  theme = theme_minimal(),
  quantile = 1.96,
  ...
)
```

Arguments

object	(mlr3::PredictionRegr).
type	(character(1)): Type of the plot. See description.
binwidth	(integer(1)) Width of the bins for the histogram.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
quantile	(numeric(1)) Quantile multiplier for standard errors for type="confidence". Default 1.96.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces("mlr3learners", quietly = TRUE)) {
library(mlr3learners)

task = tsk("mtcars")
learner = lrn("regr.rpart")
object = learner$train(task)$predict(task)

head(fortify(object))
autoplot(object)
autoplot(object, type = "histogram", binwidth = 1)
autoplot(object, type = "residual")

learner = lrn("regr.ranger", predict_type = "se")
object = learner$train(task)$predict(task)
autoplot(object, type = "confidence")
}
```

---

autoplot.ResampleResult

Plots for Resample Results

Description

Visualizations for mlr3::ResampleResult. The argument type controls what kind of plot is drawn. Possible choices are:

- "boxplot" (default): Boxplot of performance measures.
- "histogram": Histogram of performance measures.

- "roc": ROC curve (1 - specificity on x, sensitivity on y). The predictions of the individual mlr3::Resamplings are merged prior to calculating the ROC curve (micro averaged). Requires package **precrec**.
- "prc": Precision recall curve. See "roc".
- "prediction": Plots the learner prediction for a grid of points. Needs models to be stored. Set store_models = TRUE for mlr3::resample(). For classification, we support tasks with exactly two features and learners with predict_type= set to "response" or "prob". For regression, we support tasks with one or two features. For tasks with one feature we can print confidence bounds if the predict type of the learner was set to "se". For tasks with two features the predict type will be ignored.

Usage

```
## S3 method for class 'ResampleResult'
autoplot(
  object,
  type = "boxplot",
  measure = NULL,
  predict_sets = "test",
  binwidth = NULL,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(mlr3::ResampleResult).
type	(character(1)): Type of the plot. See description.
measure	(mlr3::Measure) Performance measure to use.
predict_sets	(character()) Only for type set to "prediction". Which points should be shown in the plot? Can be a subset of ("train", "test") or empty.
binwidth	(integer(1)) Width of the bins for the histogram.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	arguments passed on to precrec::autoplot() for type = "roc" or "prc". Useful to e.g. remove confidence bands with show_cb = FALSE.

Value

ggplot2::ggplot().

References

Saito T, Rehmsmeier M (2017). "Precrec: fast and accurate precision-recall and ROC curve calculations in R." *Bioinformatics*, **33**(1), 145-147. doi:10.1093/bioinformatics/btw570.

Examples

```
if (mlr3misc::require_namespaces("precrec", quietly = TRUE)) {
task = tsk("sonar")
learner = lrn("classif.rpart", predict_type = "prob")
resampling = rsmp("cv", folds = 3)
object = resample(task, learner, resampling)

head(fortify(object))

# Default: boxplot
autoplot(object)

# Histogram
autoplot(object, type = "histogram", bins = 30)

# ROC curve, averaged over resampling folds:
autoplot(object, type = "roc")

# ROC curve of joint prediction object:
autoplot(object$prediction(), type = "roc")

# Precision Recall Curve
autoplot(object, type = "prc")

# Prediction Plot
task = tsk("iris")$select(c("Sepal.Length", "Sepal.Width"))
resampling = rsmp("cv", folds = 3)
object = resample(task, learner, resampling, store_models = TRUE)
autoplot(object, type = "prediction")
}
```

---

autoplot.TaskClassif *Plots for Classification Tasks*

Description

Visualizations for mlr3::TaskClassif. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"target"` (default): Bar plot of the target variable (default).
- `"duo"`: Passes data to `GGally::ggduo()`. `columnsX` is the target and `columnsY` are the features.
- `"pairs"`: Passes data to `GGally::ggpairs()`. Color is set to target column.

Usage

```
## S3 method for class 'TaskClassif'
autoplot(object, type = "target", theme = theme_minimal(), ...)
```

Arguments

object	(mlr3::TaskClassif).
type	(character(1)): Type of the plot. See description.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces("GGally", quietly = TRUE)) {
task = tsk("iris")

head(fortify(task))
autoplot(task)
autoplot(task$clone()$select(c("Sepal.Length", "Sepal.Width")), type = "pairs")
autoplot(task, type = "duo")
}
```

---

autoplot.TaskClust *Plots for Clustering Tasks*

Description

Visualizations for mlr3cluster::TaskClust. The argument type controls what kind of plot is drawn. Possible choices are:

- "pairs" (default): Passes data GGally::ggpairs().

Usage

```
## S3 method for class 'TaskClust'
autoplot(object, type = "pairs", theme = theme_minimal(), ...)
```

Arguments

object	(mlr3cluster::TaskClust).
type	(character(1)): Type of the plot. See description.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces("mlr3cluster", quietly = TRUE)) {
library(mlr3cluster)
task = tsk("usarrests")

head(fortify(task))
autoplot(task)
}
```

---

autoplot.TaskRegr *Plots for Regression Tasks*

Description

Visualizations for mlr3::TaskRegr. The argument type controls what kind of plot is drawn. Possible choices are:

- "target" (default): Box plot of the target variable.
- "pairs": Passes data to GGally::ggpairs(). Color is set to target column.

Usage

```
## S3 method for class 'TaskRegr'
autoplot(object, type = "target", theme = theme_minimal(), ...)
```

Arguments

object	(mlr3::TaskRegr).
type	(character(1)): Type of the plot. See description.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces("GGally", quietly = TRUE)) {
task = tsk("mtcars")
task$select(c("am", "carb"))

head(fortify(task))
autoplot(task)
autoplot(task, type = "pairs")
}
```

---

autoplot.TuningInstanceBatchSingleCrit *Plots for Tuning Instances*

Description

Visualizations for mlr3tuning::TuningInstanceBatchSingleCrit. The argument `type` controls what kind of plot is drawn. Possible choices are:

- `"marginal"` (default): Scatter plots of x versus y. The color of the points shows the batch number.
- `"performance"`: Scatter plots of batch number versus y
- `"parameter"`: Scatter plots of batch number versus input. The color of the points shows the y values.
- `"parallel"`: Parallel coordinates plot. hyperparameters are rescaled by `(x - mean(x)) / sd(x)`.
- `"points"`: Scatter plot of two x dimensions versus y values. The color of the points shows the y values.
- `"surface"`: Surface plot of two x dimensions versus y values. The y values are interpolated with the supplied mlr3::Learner.
- `"pairs"`: Plots all x and y values against each other.
- `"incumbent"`: Plots the incumbent versus the number of configurations.

Usage

```
## S3 method for class 'TuningInstanceBatchSingleCrit'
autoplot(
  object,
  type = "marginal",
  cols_x = NULL,
  trafo = FALSE,
```

```
  learner = mlr3::lrn("regr.ranger"),
  grid_resolution = 100,
  theme = theme_minimal(),
  ...
)
```

Arguments

object	(mlr3tuning::TuningInstanceBatchSingleCrit.
type	(character(1)): Type of the plot. See description.
cols_x	(character()) Column names of hyperparameters. By default, all untransformed hyperparameters are plotted. Transformed hyperparameters are prefixed with x_domain_.
trafo	(logical(1)) If FALSE (default), the untransformed hyperparameters are plotted. If TRUE, the transformed hyperparameters are plotted.
learner	(mlr3::Learner) Regression learner used to interpolate the data of the surface plot.
grid_resolution	(numeric()) Resolution of the surface plot.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
...	(ignored).

Value

ggplot2::ggplot().

Examples

```
if (mlr3misc::require_namespaces(c("mlr3tuning", "patchwork", "paradox"), quietly = TRUE)) {
library(mlr3tuning)

learner = lrn("classif.rpart")
learner$param_set$values$cp = to_tune(0.001, 0.1)
learner$param_set$values$minsplit = to_tune(1, 10)

instance = ti(
  task = tsk("iris"),
  learner = learner,
  resampling = rsmp("holdout"),
  measure = msr("classif.ce"),
  terminator = trm("evals", n_evals = 10))

tuner = tnr("random_search")

tuner$optimize(instance)
```

```
# plot performance versus batch number
autoplot(instance, type = "performance")

# plot cp values versus performance
autoplot(instance, type = "marginal", cols_x = "cp")

# plot transformed parameter values versus batch number
autoplot(instance, type = "parameter", trafo = TRUE)

# plot parallel coordinates plot
autoplot(instance, type = "parallel")

# plot pairs
autoplot(instance, type = "pairs")
}
```

`plot_learner_prediction` *Plots for Learner Predictions*

Description

Visualizations for the mlr3::Prediction of a single mlr3::Learner on a single mlr3::Task.

- For classification we support tasks with exactly two features and learners with `predict_type` set to `"response"` or `"prob"`.
- For regression we support tasks with one or two features. For tasks with one feature we print confidence bounds if the predict type of the learner was set to `"se"`. For tasks with two features the predict type will be ignored.

Note that this function is a wrapper around `autoplot.ResampleResult()` for a temporary mlr3::ResampleResult using mlr3::mlr_resamplings_holdout with ratio 1 (all observations in the training set).

Usage

```
plot_learner_prediction(learner, task, grid_points = 100L, expand_range = 0)
```

Arguments

`learner`	(mlr3::Learner).
`task`	(mlr3::Task).
`grid_points`	(`integer(1)`) Resolution of the grid. For factors, ordered and logicals this value is ignored.
`expand_range`	(`numeric(1)`) Expand the prediction range for numerical features.

Value

ggplot2::ggplot().

Examples

```
if (requireNamespace("mlr3")) {
  library(mlr3)
  library(mlr3viz)

  task = mlr3::tsk("sonar")$select(c("V1", "V11"))
  learner = lrn("classif.rpart", predict_type = "prob")
  p = plot_learner_prediction(learner, task)
  print(p)
}
```

---

predict_grid *Generates a data.table of evenly distributed points.*

Description

For each point we have the predicted class / regression value in column response. If the learner predicts probabilities, a column ".prob.response" is added that contains the probability of the predicted class

Usage

```
predict_grid(learners, task, grid_points, expand_range)
```

Arguments

learners	list of trained learners, each learner belongs to one resampling iteration
task	the task all learners are trained on
grid_points	(int): see sequenize
expand_range	see sequenize

Index

as_precrec, 4
autoplot.BenchmarkResult, 4
autoplot.EnsembleFSResult, 6
autoplot.Filter, 8
autoplot.LearnerClassif, 9
autoplot.LearnerClassifCVGlmnet, 10
autoplot.LearnerClassifGlmnet *(*autoplot.LearnerClassifCVGlmnet*)*, 10
autoplot.LearnerClassifRpart, 12
autoplot.LearnerClustHierarchical, 13
autoplot.LearnerRegr, 15
autoplot.LearnerRegrCVGlmnet *(*autoplot.LearnerClassifCVGlmnet*)*, 10
autoplot.LearnerRegrGlmnet *(*autoplot.LearnerClassifCVGlmnet*)*, 10
autoplot.LearnerRegrRpart *(*autoplot.LearnerClassifRpart*)*, 12
autoplot.OptimInstanceBatchSingleCrit, 16
autoplot.PredictionClassif, 18
autoplot.PredictionClust, 20
autoplot.PredictionRegr, 21
autoplot.ResampleResult, 22
autoplot.ResampleResult(), *29*
autoplot.TaskClassif, 24
autoplot.TaskClust, 25
autoplot.TaskRegr, 26
autoplot.TuningInstanceBatchSingleCrit, 27

bbotk::OptimInstanceBatchSingleCrit, *16, 17*

EnsembleFSResult, *6*

GGally::ggduo(), *24*
GGally::ggpairs(), *24–26*
ggfortify::autoplot.kmeans, *20*
ggplot2::ggplot(), *5*, *7–9*, *11*, *13*, *14*, *16*, *17*, *19*, *20*, *22*, *23*, *25–28*, *30*
ggplot2::theme(), *5*, *7–9*, *11*, *13*, *14*, *16*, *17*, *19*, *20*, *22*, *23*, *25*, *26*, *28*
ggplot2::theme_minimal(), *5*, *7–9*, *11*, *13*, *14*, *16*, *17*, *19*, *20*, *22*, *23*, *25*, *26*, *28*

mlr3::BenchmarkResult, *4*, *5*
mlr3::Learner, *4*, *16*, *17*, *27–29*
mlr3::LearnerClassif, *9*
mlr3::LearnerClassifRpart, *12*, *13*
mlr3::LearnerRegr, *15*
mlr3::LearnerRegrRpart, *13*
mlr3::Measure, *5*, *19*, *23*
mlr3::mlr_resamplings_holdout, *29*
mlr3::Prediction, *29*
mlr3::PredictionClassif, *18*, *19*
mlr3::PredictionRegr, *21*, *22*
mlr3::resample(), *23*
mlr3::ResampleResult, *22*, *23*, *29*
mlr3::Resampling, *5*, *23*
mlr3::Task, *4*, *5*, *9*, *11*, *13–15*, *29*
mlr3::TaskClassif, *24*, *25*
mlr3::TaskRegr, *26*
mlr3cluster::LearnerClustAgnes, *14*
mlr3cluster::LearnerClustDiana, *14*
mlr3cluster::LearnerClustHclust, *14*
mlr3cluster::PredictionClust, *20*
mlr3cluster::TaskClust, *20*, *25*, *26*
mlr3filters::Filter, *8*
mlr3fselect::EnsembleFSResult, *6*
mlr3learners::LearnerClassifCVGlmnet, *11*
mlr3learners::LearnerClassifGlmnet, *10*, *11*
mlr3learners::LearnerRegrCVGlmnet, *11*
mlr3learners::LearnerRegrGlmnet, *11*

mlr3tuning::TuningInstanceBatchSingleCrit, *27*, *28*
mlr3viz *(*mlr3viz-package*)*, 3
mlr3viz-package, 3

plot_learner_prediction, 29
precrec::autoplot(), *5*, *23*
precrec::evalmod(), *4*
precrec::mmdata(), *4*
predict_grid, 30

stabm::listStabilityMeasures(), *7*